

SHELL SCRIPTING,
CROND, ATD

SHELL SCRIPTING

- Shell scripting involves placing a series of shell commands in a file for later re-use.
 - Simple shell scripts simply run command after command, as if the user typed them in at the command line
 - More complex shell scripts actually make decisions about what commands need to be run, and might even repeat certain sequences to accomplish some task
- Scripts start executing at the top and stop when there are no more commands to execute or when `exit` is called.

EXAMPLE SHELL SCRIPT

- Here is an example of a very simple shell script:

```
echo "Hello, what is your name?"  
read NAME  
echo "Hello $NAME, it's nice to meet you!"  
echo -n "The current time is: "  
date
```

- Using the `echo` command, this script asks a question.
- The `read` command accepts input from the user and stores it in the environment variable `NAME`
- The script finishes up with a couple more `echo` statements, greeting the user and announcing today's date

SHELL SCRIPTING

- If we put the example in a file called `myscript`, we can execute the script as:
 - `bash myscript`
- `bash` will open `myscript` and execute each line as if the user had typed it in manually.

```
[root@localhost ~]# bash myscript
Hello, what is your name?
Linus
Hello Linus, it's nice to meet you!
The current time is: Sun Nov 29 09:39:33 CST 2009
[root@localhost ~]#
```

INTERPRETERS

- In the previous example, we put five commands in a regular file and fed the filename to `bash` on the command line, which in turn executed the commands.
- Running in this way, `bash` operated as an interpreter. Reading each line of the file, `bash` would interpret the words and perform some action.
- There are many interpreted languages available for scripting, including all shells, `python`, `ruby`, `perl`, etc.

EXECUTING SCRIPTS

- To run a script, feed the file to the appropriate interpreter:
 - `bash mybashscript`
 - `perl myperlscript`
- This works fine, but sometimes it's more user-friendly to allow the script to be run directly, removing the need for an external call to the interpreter...
 - `./mybashscript`
 - `myperlscript`

SHEBANG

- This is accomplished with the shebang (`#!`). Also known as a hash bang, pound bang or hashpling.
- When the kernel is asked to execute a file, it must either be machine code, or a file that starts with the shebang sequence. If the first two characters of the file are a hash mark and an exclamation mark, the rest of the line is expected to be an absolute pathname for an interpreter, which will then be invoked to “run” the file as a script.

SHEBANG

- So, add an appropriate shebang to the example:

```
#!/bin/bash
echo "Hello, what is your name?"
read NAME
echo "Hello $NAME, it's nice to meet you!"
echo -n "The current time is: "
date
```

- Then add execute permissions and the script can be run directly:

```
[root@localhost ~]# chmod 755 myscript
[root@localhost ~]# ./myscript
Hello, what is your name?
Linus
Hello Linus, it's nice to meet you!
The current time is: Sun Nov 29 09:39:33 CST 2009
[root@localhost ~]#
```


SCRIPTING

- There is of course quite a bit more to shell scripting than can be covered in this course. There are a few more structures you can use for looping, and dozens of special metacharacters for achieving all kinds of results.
- With this introduction, though, you should be able to read through light shell scripts and have a handle on what's going on, as well as be able to write simple ones on your own.

CROND

Scheduled fun

OVERVIEW

- `crond` is the cron daemon. Cron provides for the ability to execute commands on a regular basis.
- Generally used to run hourly, daily and weekly type system maintenance scripts.
- Also useful to run reports, cleanup jobs and much, much more.

USING CRON

- Cron is controlled through crontab files.
 - There are system-wide crons, accessible under `/etc/cron.*`
 - Every user has their own crontab, accessible through the `crontab` command

SYSTEM CRONS

- `/etc/crontab` defines the system cron jobs.
 - Many distributions use the `run-parts` script to execute all scripts found in `/etc/cron.hourly`, `/etc/cron.daily`, etc on the appropriate schedule.
 - `/etc/crontab` defines the times for each schedule: hourly, daily, weekly, monthly

CRONTAB

- `crontab`: View, edit or remove crontabs
 - The `-l` option prints the crontab. The `-e` option opens the crontab for editing. The `-r` option removes the crontab.
 - Root can work with the crontab for any user by specifying the username on the command line:
 - `crontab -e -u bob`

Crontab Syntax

- There are two main components to a crontab entry:
 - The timespec specifies when the command should be run
 - The command is what gets executed every time the timespec is matched

CRONTAB TIMESPECS

- The timespec is broken down into 5 fields, separated by spaces:
 - minute hour day-of-month month day-of-week
- Each field can contain a number, a range of numbers, a comma-separated list of numbers, an asterisk or a number slash division rate
- Mostly self-explanatory - some examples will help...

TIMESPEC EXAMPLES

- 0 23 * * * *11pm every day*
- 30 * * * 1-5 *30 minutes after every hour, M-F*
- 0 7 1 * * *7am, first of every month*
- * * * * * *Every single minute*
- 0,10,20,30,40,50 * * * * *Every 10 minutes*
- */5 8-17 * * 1-5 *Every 5 minutes, 8am-5pm, M-F*

EXAMPLE CRONTAB

```
01 4 * * * /usr/local/bin/restart-webserver  
00 8 1 * * /usr/bin/mail-report boss@mycompany.com  
*/5 * * * * /monitor/bin/check-site -e admin@mycompany.com -o /var/log/check.log
```

- There are various additional options and features available to the cron system. Check the man pages for reference:
 - `cron`, `crontab` (sections 1 and 5)

ATD

ATD OVERVIEW

- `atd` is a simple daemon that executes one-off jobs at a certain time.
- To create an at job:
 - `at <time>`
 - Then you enter all of the commands you want run at the given time, and finish by typing `ctrl-d`

ATD

- atd is not commonly used these days, but if it's there it can be useful in some situations..
- If editing the firewall on a machine over the network, it's sometimes nice to put a simple "reset" so if you lock yourself out, you'll be able to get back in the machine:

```
[root@localhost ~]# at now + 10 minutes
at> iptables-save > /iptables.backup
at> iptables -F
at> <EOT>
job 1 at 2009-11-30 10:44 a root
[root@localhost ~]#
```

ATD

- Some additional commands to use with the at system:
 - `atq`: Displays list of at jobs
 - `atrm`: Removes given at job from queue

```
slideshow.end();
```