

RHCSA

BOOT CAMP

Users and Groups

USERS AND GROUPS

- Users and Groups define access to the operating system through the file permission scheme.
- Root is the super user, and the only user with special permissions
- Every user is a member of at least one group, which is called their primary group. The main purpose of this primary relationship is to define group owner of created files.
- Users can have a secondary group membership in as many groups as needed. These secondary relationships exist to broaden a user's access to the files on the system.

CONFIG FILES

- User information is stored in two files:
 - `/etc/passwd`
 - `/etc/shadow`
- Group information is stored in one file:
 - `/etc/group`

/ETC/PASSWD

- List of user records, one per line, with columns separated by colons. Format:
- `login:x:userid:groupid:gecos:homedir:shell`
- Examples:
 - `root:x:0:0:root:/root:/bin/bash`
 - `mysql:x:27:27:MySQL Server:/var/lib/mysql:/bin/bash`

/ETC/SHADOW

- Similar colon-separated-column list of records:
- `login:password:password aging fields`
- Aging fields track dates for password resets, locks, etc
- Examples:
 - `root:pB8msP1fCbCqc:13904:0:99999:7:::`
 - `nisburgh:vRoPw6a/jQsp.:14466:0:99999:7:::`

/ETC/GROUP

- Same colon-separated-column list of records format
- `groupname:grouppassword:groupid:secondarymembers`
- Group passwords allow temporary management to a group, are rarely used and not set up by default
- Examples:
 - `daemon:x:2:root,bin,daemon`
 - `apache:x:48:jack,nisburgh`

MANAGEMENT

- While it is possible to edit the three files directly, it's easier and safer to use the management commands to create, modify and delete users and groups:
 - `useradd, usermod, userdel`
 - `groupadd, groupmod, groupdel`

USERADD

- `useradd`: Add a new user to the system
- Accepts various arguments to control the settings on the user account. Most common is the `-g` option to specify the primary group of the user, and the `-G` option to list secondary group memberships. Examples:
 - `useradd lisa`
 - `useradd -g clowns -G trouble,simpson bart`

USERMOD, USERDEL

- `usermod`: Modify a user's settings. Example:
 - `usermod -G detention bart`
- `userdel`: Remove a user from the system. Main option to consider is `-r`, which tells `userdel` to remove the user's home and spool directories. Example:
 - `userdel moe`

GROUP COMMANDS

- `groupadd`: Adds a new group to the system. Example:
 - `groupadd bullies`
- `groupmod`: Mainly used to rename a group. Example:
 - `groupmod -n mktg mkg`
- `groupdel`: Remove a group. Example:
 - `groupdel microsoft`

PASSWORDS

- `passwd`: Change login password.
- Root can change the password for any user on the system
- Root can also setup password aging, allowing for timed password resets and account disabling (or use `chage`)
- `passwd` is also the preferred way to lock a user account:
 - `passwd -l mary`

PASSWORD AGING

- To set the maximum lifetime for a user's password:
 - `passwd -x days login`
- When a user's password has expired, you can set the number of days it can remain expired before disabling the account completely:
 - `passwd -i days login`

IMPORTANT USER ENVIRONMENT FILES

- `/etc/skel` default template for a newly-added user's home directory
- `/etc/profile` sets environmental variables used by all users
- `/etc/profile.d` contains scripts specific to certain rpms
- `/etc/bashrc` contains global aliases and system settings
- `~/.bashrc` contains user aliases and functions
- `~/.bash_profile` contains user environment settings and can be set to automatically start programs at login

LAB

1. Create a new group `dev`. Create a new user `alice` as a member of the `dev` group, with a description of “Alice from Dev” and a default shell of `/bin/csh`. Use the `passwd` command to set a password for `alice`, then log in as `alice` and verify her access.
2. Set a maximum password lifetime of 4 weeks for the `alice` account. Look at the `passwd`, `shadow` and `group` files.
3. Configure the users `guido`, `linus`, and `richard`. Set all their passwords to “`linux`”.
4. Make these users part of the `ru` group.
5. Configure the directory `/home/linux` so that each user from the `ru` group can read, create, and modify files.
6. Configure the directory `/home/linux/work` so that each user can create and read files, but only the file’s owner can delete.
7. Use ACL’s to allow `alice`, not in `ru`, full r/w access to the `work` folder.

NIS

- NIS Servers can be configured to centrally manage system and account information. These servers can share the contents of `/etc/passwd`, `/etc/shadow`, `/etc/group`, and several other files among any number of clients.
- To configure a client, you must install the `ypbind` and `portmap` RPMs, and then you can run `system-config-authentication`.
- This command will make the proper entries in:
 - `/etc/sysconfig/network`
 - `/etc/yp.conf`
 - `/etc/nsswitch.conf`
 - `/etc/pam.d/system-auth`

LAB

1. Configure your server to authenticate against `server1.example.com` using NIS.
2. You should then be able to log in to your server as `station#` (where # is your station number) with the password: `station#`

LDAP

- LDAP Servers can also be configured to centrally manage system and account information. LDAP is much more secure and flexible than a default NIS configuration, and as such is becoming much more popular.
- To configure a client, you must install the `nss-pam-ldapd` and `openldap` RPMs, and then you can run **`system-config-authentication`**.
- This command will make the proper entries in:
 - `/etc/ldap.conf`
 - `/etc/openldap/ldap.conf`
 - `/etc/nsswitch.conf`
 - `/etc/pam.d/system-auth`

LAB

1. Disable NIS authentication and verify you can no longer authenticate as `station#`.
2. Configure your server to authenticate against `server1.example.com` using LDAP.
3. You should then be able to log in to your server as `station#` (where # is your station number) with the password: `station#`


```
slideshow.end();
```